



| SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION | | | |
|--|---|--------------------------|-------------------|
| Product Name | WS-10 | Code | 1374 |
| Supplier | Trican Well Service Ltd. 2900, 645 – 7 th Ave S.W. Calgary, Alberta, T2P 4G8 For Product Information/MSDS Call: 403-266-0202 or 403-723-3688 (8:00 AM – 5:00 PM MST, Monday – Friday) | Revision Date | July 7, 2011 |
| Product Uses | Wax solvent | Supersedes Date | November 17, 2008 |
| 24 Hour Emergency Numbers | CANUTEC 613-996-6666 (Canada 24 hours) | Original Creation | June 1, 1998 |

| SECTION 2. HAZARDS IDENTIFICATION | |
|---|---|
| WHMIS (Pictograms) | Workplace Hazardous Material Information System Classification |
|   | B2 Flammable Liquid D2A Very toxic material causing other toxic effects D2B Toxic material causing other toxic effects |
| Hazard Summary | <p>DANGER! HIGHLY FLAMMABLE. EYE AND SKIN IRRITANT. HARMFUL IF INHALED. ASPIRATION HAZARD. MAY CAUSE FETOTOXIC EFFECTS. MAY CAUSE CANCER.</p> <p>Avoid excessive heat, open flames, sparks and ignition sources. Liquid can release vapors that readily form flammable mixtures at or above the flashpoint. Vapours are heavier than air and may travel considerable distances to a source of ignition and flash back. Vapours may spread along the ground and enter sewers, basements and other low lying spaces. Product will float on water.</p> <p>Bond and ground containers before transferring material. Product can accumulate static charge which may cause a fire or explosion.</p> <p>Use only with adequate ventilation. Avoid breathing vapour or mist. Inhalation of vapours may cause respiratory irritation, headache, dizziness, nausea, loss of consciousness, and in cases of extreme exposure, possibly death.</p> <p>Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. This product is an eye irritant and, on prolonged or repeated contact, a skin irritant.</p> <p>This is a low viscosity material - if swallowed, it may be aspirated and can cause serious or fatal lung damage. Do not ingest.</p> <p>Spilled material will be slippery and may cause falls.</p> |
| Routes of Exposure | Eyes, skin, inhalation and ingestion. |
| Potential Acute Health Effects | |
| Eyes Contact | Direct liquid contact with eyes will cause irritation. Vapour and mist may cause eye irritation. |
| Skin Contact/Absorption | Irritating to skin. Prolonged or repeated contact may cause drying and defatting of the skin resulting in dermatitis. |
| Inhalation | Inhalation of vapours may cause irritation, headaches, loss of appetite, peripheral neuropathy, insomnia, drowsiness, bone marrow damage. Inhalation of vapours may also affect the Central Nervous System, bone marrow, liver and kidneys. |

| | |
|--|---|
| Ingestion | Ingestion may lead to vomiting and diarrhea. Vomiting may cause aspiration of liquid into the lungs and may result in chemical pneumonia, severe lung damage and respiratory failure. |
| Medical Conditions Aggravated by Exposure | Neurological and cardiovascular disorders, diseases of the skin, eyes or respiratory tract, preexisting liver and kidney disorders. |
| <i>See also Toxicological Information (Section 11)</i> | |
| Additional Remarks | None |

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

| Name | CAS # | % (wt) |
|---------------------------|-----------|---------|
| Low boiling point naphtha | 8032-32-4 | 60-100 |
| n-hexane | 110-54-3 | 10-30 |
| toluene | 108-88-3 | 1-5 |
| xylene, mixed isomers | 1330-20-7 | 0.1-1.5 |
| ethyl benzene | 100-41-4 | 0.1-1.5 |
| benzene | 71-43-2 | 0.1-1.5 |

SECTION 4. FIRST AID MEASURES

| | |
|---------------------------|---|
| Eye Contact | Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. If irritation persists, repeat flushing. Seek immediate medical attention. |
| Skin Contact | Remove contaminated clothing and launder before reuse. Wash contaminated skin with mild soap and water for at least 15 minutes. If irritation persists, repeat flushing. Seek immediate medical attention. |
| Inhalation | Remove person to fresh air. If breathing has stopped, trained personnel should begin artificial respiration (AR) immediately. If heart has stopped, trained personnel should begin cardiopulmonary resuscitation (CPR) immediately. Seek immediate medical attention. |
| Ingestion | Do NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of material into lungs. Never give anything by mouth to an unconscious person. Seek immediate medical attention. |
| Notes to Physician | The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. |
| Additional Remarks | None |

SECTION 5. FIRE FIGHTING MEASURES

| | |
|--|--|
| Conditions of Flammability | Flammable liquid. When heated above the flashpoint, readily releases flammable vapours. When mixed with air and exposed to ignition source, vapours can burn in open or explode if confined. Vapours are heavier than air. Vapours can travel along ground and flashback along vapour trail. Product will float, is capable of creating a fire hazard along the path of runoff and can be reignited on the surface of water. Containers exposed to intense heat may rupture. |
| Extinguishing Media | Use dry chemical, carbon dioxide, foam or water fog. Do not use solid water stream as it may scatter material and spread the fire. Water spray may be used to cool containers exposed to fire conditions. |
| Protection of Firefighters | As in any fire, wear full fire fighting gear including NIOSH-approved positive pressure self-contained breathing apparatus. |
| Hazardous Combustion Products | Carbon dioxide, carbon monoxide, and irritating gases including sulfur dioxide may be formed upon combustion. Product burns with a very smoky flame. |
| Sensitivity to Static Discharge | This product is sensitive to static discharge. Bond and ground all containers before transferring material. |
| Additional Remarks | None |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | |
|----------------------------------|--|
| Personal Precautions | Eliminate all ignition sources. Isolate hazard area and restrict access. Try to work upwind of spill. Do not touch or walk through spilled material. Spilled material is slippery. Do not breathe vapor or mist. Provide adequate ventilation. Ventilate closed spaces before entering. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8). Shut off leak only if it can be done safely. |
| Environmental Precautions | Prevent substance from entering natural bodies of water and sewer systems. |

| | |
|---------------------------|---|
| Clean Up Methods | Spilled product may pose a risk to the aquatic ecosystem if released. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding all equipment. Monitor area with combustible gas indicator. Use spark-proof tools and explosion-proof equipment. Move containers from spill area. Absorb small spills with an inert material. For large spills, contain with dikes and collect spillage by pumping off or absorb with a non-combustible material (e.g. sand, earth, vermiculite or diatomaceous earth). Place residues in a suitable, covered, properly labeled container for disposal according to local regulations. Contaminated absorbent material and soil may pose the same hazard as the spilled product. |
| Additional Remarks | Waste must be disposed of in accordance with federal, provincial and local environmental control regulations. |

SECTION 7. HANDLING AND STORAGE

| | |
|-----------------------------|---|
| Fire Prevention | Handle as a flammable liquid. Keep away from heat, open flames, sparks and other sources of ignition. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Empty containers may contain flammable product residue. Do not reuse container. Do NOT cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity or other sources of ignition. |
| Worker Contact | Wear appropriate personal protective equipment. Avoid prolonged or repeated skin contact. Avoid breathing vapours or mists. Use only with adequate ventilation. Maintain good personal hygiene. Do not smoke, eat or drink when handling this product. Wash thoroughly after handling product and before eating, drinking or smoking. |
| Storage Requirements | Store in a cool, dry, well-ventilated area, away from heat, ignition sources, and incompatible materials. Keep container tightly closed when not in use. |
| Additional Remarks | None |

SECTION 8. EXPOSURE CONTROL/PERSONAL PROTECTION

| | |
|---|--|
| Exposure Guidelines / Limits | Not established for product. |
| Exposure Guideline / Limits for Components | |
| n-hexane | ACGIH TLV: TWA 50 ppm; absorbed through skin contact; |
| heptane | ACGIH TLV: TWA 400 ppm; STEL 500 ppm ; |
| octane | ACGIH TLV: TWA 300 ppm; |
| methylcyclohexane | ACGIH TLV: TWA 400 ppm; |
| n-nonane | ACGIH TLV: TWA 200 ppm; |
| toluene | ACGIH TLV: TWA 20 ppm; |
| xylene, mixed isomers | ACGIH TLV: TWA 100 ppm; STEL 150 ppm |
| ethyl benzene | ACGIH TLV: TWA 100 ppm; STEL 125 ppm; |
| benzene | ACGIH TLV: TWA 0.5 ppm; STEL 2.5 ppm ; absorbed through skin contact |
| Please consult with local authorities for acceptable local exposure limits since values can vary from jurisdiction to jurisdiction. | |
| Engineering Controls | Provide exhaust ventilation or other engineering controls to keep the airborne concentrations below their respective occupational exposure limits. Mechanical ventilation is required for all indoor situations to control fugitive emissions. Electrical and mechanical equipment should be explosion-proof. |
| Personal Protection | |
| Personal Protective Equipment recommendations are based on anticipated known manufacturing and use conditions. These conditions are expected to result in only incidental exposure. A thorough review of the job tasks and conditions by a safety professional is recommended, however, to determine the level of person protective equipment appropriate for these job tasks and conditions. | |
| Respirator | If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. A NIOSH-approved air-purifying mask equipped with organic vapor cartridges with P95 prefilters may be appropriate. In poorly ventilated areas or emergency situations use a NIOSH-approved atmosphere-supplying respirator. |
| Hands | Nitrile or neoprene gloves. |
| Eyes | Chemical safety goggles and/or face shield if splashing may occur during handling. |
| Body | Wear long sleeves and pants to prevent prolonged or repeated skin contact. Remove contaminated clothing and launder before reuse. |
| Feet | Steed toed, chemical resistant boots. |

Other Eyewash stations and safety showers are near the work location.

Protective Clothing (Pictograms)



Additional Remarks None

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------------------|--|
| Physical State | Liquid |
| Appearance and Odour | clear & colourless oily with hydrocarbon odour |
| Odour Threshold | Not available |
| Specific Gravity | 0.72 – 0.75 (varies with source) |
| Flashpoint | -18 °C (-0.4 F) (method not specified) |
| Lower Flammable Limit | Not available |
| Upper Flammable Limit | Not available |
| Autoignition Temperature | Not available |
| Vapour Density (air=1) | >1 |
| Vapour Pressure | 22.3 kPa Reid Vapour Pressure |
| Evaporation Rate | 0.76 (n-butyl acetate = 1) (ASTM D3539) |
| Boiling Point | 37°C (98.6 F) |
| Freezing/ Point Point | Not available |
| pH | Not applicable |
| Viscosity | Not available |
| Solubility in Water | Insoluble in water. |
| Coefficient of Water/Oil | Not available |
| Additional Remarks | None |

SECTION 10. STABILITY AND REACTIVITY DATA

| | |
|---|---|
| Chemical Stability | Material is stable under normal conditions. |
| Hazardous Polymerization | Will not occur |
| Sensitivity to Mechanical Impact | No |
| Incompatible Material | Strong oxidizing agents. |
| Conditions of Reactivity | Avoid high temperatures, open flames, sparks, welding, smoking and other ignitions sources. |
| Hazardous Decomposition Products | Not available |
| Additional Remarks | None |

SECTION 11. TOXICOLOGICAL INFORMATION

| | |
|--------------------------------------|---|
| Acute Toxicity | Not available for product. |
| Acute Toxicity for Components | |
| Ligroine | LC50 (inhalation, rat): 3400 ppm/4hr estimate |
| n-hexane | LD50 (oral, rat): 28,710 mg/kg LC50 (inhalation, rat): 48,000 ppm / 4hr |
| toluene | LD50 (oral, rat): 5000 mg/kg LC50 (inhalation, rat): 8000 ppm / 4hr |
| xylene, mixed isomers | LD50 (oral, male rat): >4300 mg/kg LD50 (dermal, rabbit): >1700 mg/kg LC50 (inhalation, rat): 5000 ppm/4hr |
| ethyl benzene | LD50 (oral, male rat): 3500 mg/kg LD50 (dermal, rabbit): >5000 mg/kg LC50 (inhalation, rat): >4000 ppm /4hr |
| benzene | LD50 (oral, rat): 3306 mg/kg LC50 (inhalation, rat): 7000 ppm / 7hr |
| Effects of Acute Exposure | See <i>Hazards Identification (Section 2)</i> |
| Effects of Chronic Exposure | Prolonged or repeated exposure to the skin can defat the skin and lead to dermatitis. Inhalation may cause headaches, loss of appetite, drowsiness, visual impairment, peripheral neuropathy, insomnia, drowsiness, bone marrow damage and may also affect the Central Nervous System, liver and kidneys. |
| Irritancy of Product | See <i>Hazards Identification (Section 2)</i> |
| Skin Sensitization | Not expected |
| Respiratory Sensitization | Not expected |
| Carcinogenicity | This product contains benzene. The International Agency for Research on |

| | |
|---------------------------------------|--|
| | <p>Cancer (IARC) has evaluated benzene and classified it as carcinogenic to humans (Group 1). ACGIH has classified benzene as a confirmed human carcinogen (A1).</p> <p>This product contains ethyl benzene. The International Agency for Research on Cancer (IARC) has evaluated ethyl benzene and classified it as possibly carcinogenic to humans (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. ACGIH has classified ethyl benzene as a confirmed animal carcinogen with unknown relevance to humans (A3).</p> |
| Reproductive Toxicity | Not available. |
| Teratogenicity/ Embryotoxicity | Toluene and xylene have produced fetotoxic effects in animals, in the absence of maternal toxicity. |
| Mutagenicity | Not available |
| Synergistic Products/Effects | The toxicity of this material is probably increased by exposure to other solvents, alcohols or aromatic hydrocarbons, which inhibit their breakdown by the liver. Xylene reacts synergistically with n-hexane to enhance hearing loss. |
| Additional Remarks | None |

SECTION 12. ECOLOGICAL INFORMATION

| | |
|---------------------------|--|
| Ecotoxicity | If released into soil, it will absorb and may biodegrade in anaerobic conditions. Photo-oxidation products include phenol, nitrophenols, nitrobenzene, formic acid and peroxyacetyl nitrate. Runoff from fire control or dilution water may cause pollution. Do not contaminate domestic or irrigation water supplies, lakes, streams, ponds, or rivers. |
| Degradability | Not available |
| Bioaccumulation | Not available |
| Mobility | Not available |
| Additional Remarks | None |

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use, dilution or contamination of this product may cause its physical and chemical properties to change. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Dispose in accordance with federal, provincial and local regulations.

Dispose of all packaging in accordance with local regulations. Empty containers may contain residue and should be completely drained and safely stored until appropriately reconditioned or disposed. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Additional Remarks None

SECTION 14. TRANSPORT INFORMATION

TDG Classification

PETROLEUM DISTILLATES, N.O.S., Class 3, UN1268, PG II



| | |
|---|---------------|
| Marine Pollutant | Not available |
| Additional Transport Information | None |
| Emergency Response Guide | 128 |

SECTION 15. REGULATORY INFORMATION

Canadian Regulations

WHMIS This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

DSL Inventory All components of this product are either on the Domestic Substances List (DSL), the Non-Domestic Substances List (NDSL) or exempt.

TSCA Inventory Status All components are included or are exempted from listing on the US Toxic Substances Control Act Inventory.

Additional Remarks None

SECTION 16. OTHER INFORMATION

| | |
|--------------------|--|
| Revisions | July 7, 2011: Format changes. Formulation has been changed. Information has been revised throughout. Changes to WHMIS and transport classifications. |
| Prepared by | Trican Well Service Corporate Health, Safety & Environment Department (403) 723-3688 |

Trican Well Service Ltd. Disclaimer

NOTE: The information on this MSDS is based on data which is considered to be accurate. Trican Well Service Ltd., however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. This MSDS was prepared and is to be used for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

END OF MATERIAL SAFETY DATA SHEET